

**Fire Protection & Insulation Solutions** 

20 Dobra Road Yangebup, WA 6164 Ph: +61 8 9418 8826 Mobile: +61 402 002 359

Mobile: +61 402 002 359 Email: sales@darco.com.au

## **TECHNICAL DATA SHEET**

## E Glass Insulation Tapes Style DELT series Description and Advantages

**DELT series** E glass tapes are a non-asbestos product, manufactured from highly texturized yarns, specially developed for high temperature applications. These tapes are produced from closely (tight) woven yarns, enabling tapes to be produced which retain a high degree of softness and flexibility. Applications include thermal and electrical insulation wrap; gasket seals etc. E glass tapes are resistant to oils, solvents and most chemicals, but direct contact with live steam should be avoided.

**Ladder tape** is made by removing yarns through the center of the woven tape, creating a ladder effect. These tapes are useful in the sealing of furnaces, ovens and where bolt-holes are required in fabrication.



Service Temperature Constant Max	550°c , E glass woven tape
Melting Temp.	800°c
Physiologically Harmless refer MSDS	Yes
Combustibility	Non combustible
Yarn	E glass continuous filament-texturized fiber
Coating/finishes	Ladder

## **Current Product Stock Range Selection Chart**

**DELT Series: Plain Tight Woven E glass Ladder Tapes** 

E GLASS WOVEN LADDER TAPES 3mm Thick		Mtrs/Roll	unit
DELT403	Woven 40mm x 3mm	30	Roll
DELT503	Woven 50mm x 3mm	30	Roll
DELT753	Woven 75mm x 3mm	30	Roll