

Fire Protection & Insulation Solutions

20 Dobra Road, Yangebup, WA 6164 Ph: +61 8 9418 8826 Mobile: +61 402 002 359

Mobile: +61 402 002 359 Email: sales@darco.com.au

TECHNICAL DATA SHEET

DSSFT SeriesSilicone Self Fusing Tape

Darco Silicone Self Fusing tape has no adhesives. It bonds to itself upon contact forming an airtight, waterproof seal. It's easily removed since there is no adhesive. It's a better alternative to electrical tape. Originally developed by the military, this tape can be used in a huge variety of applications. Weatherproofing, Corrosion Protection, Leak Stopping, High Voltage Insulation, Sector Identification, Wire Harnessing....and Much More!



Length	5m	10m, 5m
Width	25mm	50mmx10m, 100mmx5m
Thickness	0.5mm	0.5mm
Temperature Range	-54°C to 260°C	-54°C to 260°C
Physiologically Harmless	Yes	Yes
Elasticity	Stretches to 300% of its original size	Stretches to 300% of its original size
Colour	Oxide Red and Black	Oxide Red

Waterproof, Resists UV, Oil, Salts, and Corrosive Chemicals, Insulates 400V per Mil, Leaves no residue, UL Listed

Meets or exceeds U.S. Military Spec AA-59163 (formerly MIL I-46852C) Type II, Triangular Guideline and Type I, Rectangular Self-Fusing Silicone Rubber Tape

Other sizes & Colours available upon request – MOQ may apply