

Darco Fire retardant Hook and Loop sew on Nylon tapes

Description and Advantages



TECHNICAL DATA SHEET		DEPARTMENT	QUALITY DEPARTMENT
FIRE RETARDANT HOOK AND LOOP		FILE NO.	WI-QC-098
		FIVE VERSION	A0
		PAGE	01/01
PRODUCT NAME	FR HOOK AND LOOP		
MATERIAL	NYLON (POLAMIDE)		
CONSTRUCTION	WOVEN		
STANDARD BINDER BACKING	SYNTHETIC RESIN		
SPECIAL TREATMENT	FIRE RETARDANT		
OVERALL THICKNESS	1.70-2.05MM		
WEIGHT/M2	330G ±10%		
LENGTH	25METERS PER ROLL (REQUEST 25.15-25.25M), OR AS REQUEST		
WIDTH	WIDTH	50±1MM	
PEEL STRENGTH	AVG = 2.0N/CM	MIN = 1.5 N/CM	
SHEAR STRENGTH	AVG = 10.0N/CM2	MIN=7.5N/CM2	
CYCLE LIFE	10% LOSS AFTER 1000 TIME USE		
	30% LOSS AFTER 2000 TIME USE		
	40% LOSS AFTER 5000 TIME USE		
	50% LOSS AFTER 10000 TIME USE		
	60% LOSS AFTER 20000 TIME USE		
COLOURFASTNESS	4 MINIMUM		
Service Temperature	70°C		
Short Term Temperature	199°C		