

**Fire Protection & Insulation Solutions** 

20 Dobra Road, Yangebup 6164

Ph: +61 8 9418 8826 Mobile: +61 402 002 359 Email: sales@darco.com.au

## **TECHNICAL DATA SHEET**

# Sewing Thread Style KEV/SS/THREAD Description and Advantages



Darco style **KEV/SS/THREAD** is a high performance sewing thread made from a special steel core with 10 steel wires wrapped with a para-aramid cover. It has been designed as a sewing thread for a broad range of technical textiles offering a superior level of temperature resistance. The

special steel core can withstand temperatures of approximately 600°C under mechanical strain and up to 1000°C without any mechanical strain. It also provides good sewing performance, and is manufactured by the largest global thread supplier.



#### Main Uses:

- Welding blankets and curtains
- Fire curtains
- Insulation jackets
- Thermal covers

- Heat and flame protective carpets, mats and tarpaulins
- Firefighter uniforms
- Flame retardant protective clothing

### **Technical Specification:**

Tex No	Ticket No Nm	Ply	Average Strength		Elongation % Min - Max	No of steel	Recommended Needle Size*	
			cN	Grams		wires	Singer	Metric
210	13	1	6,000	6,118	6-10	10	21 - 23	130 - 160

<sup>\*</sup> Needle size recommendations are a guide only and ultimately depend on the sewing application.

Since conditions and applications vary considerably in the use of thread, the thread user should assure herself or himself by preliminarily testing that the thread is suitable for the end use intended. Technical information listed above is based on current averages and should be taken only as indicative.

#### **Additional Information:**

Darco KEV/SS/THREAD sewing thread is suitable for use in heat and fire fighters' protective clothing according to EN ISO 11612, EN ISO14116 and EN 469. They are not suitable for use in protective clothing for electricians and welders as the relatively low vertical resistance (< 105\_) material cannot guarantee protection from the possibility of electrical shock by contact with live electric conductors